

Fire Fighting Diesel Engine

Auto Start Panel



Car-Mel
ENHANCING FIRE PROTECTION

CARMEL SENSORS PVT. LTD.

WWW.CARMEL.CO.IN



Fire Fighting Diesel Engine Auto Start Panel

Description

The Diesel Engine Auto Start Panel is intended to start the Diesel Engine driven pump automatically when the water line pressure in the hydrant system is below a specified level. It is wall mounted type, Fabricated out of 16 SWG CRCA .The panel is powder coated with required colour shade. The panel is easy maintenance and operation. The Panel is provided with a simple charger Equipment, Auto Start Timers, Necessary relays, Selector Switches Indicating Lamps and Push buttons.

Specifications

Primary Power	12 V / 24 V DC
Operating Voltage	12 V / 24 V DC
Operating Environment	-10 to 45° C, 30-95% RH.
Charger Type	TRICKLE / BOOST
Charger Voltage	12 V / 24 V
Charger Current	3 A
Charger Fuse	6 A
Dimensions	(L) 480 (B) 200 (H) 600.

108, Electronic Industrial Estate, Perungudi, Chennai - 600 096. India.
Ph: +91-44-2496 0838, Fax: +91-44-24961139 E-mail: marketing@carmel.co.in

Website: www.carmel.co.in